

# **AN-80i**

**Advanced Broadband Wireless Infrastructure Solution** 



The AN-80i broadband wireless radio provides high capacity, long range point-to-point and point-multipoint communications links wherever needed. Chosen for its ability to deliver a seamless wireless experience in complex applications, the AN 80i is used throughout the world by service providers, governments, oil and gas industry, utilities, and military organizations.

Powered by Redline's, innovative third generation Orthogonal Frequency Division Multiplexing (OFDM) technology, the AN-80i radio is an IEEE 802.16 standards based design with powerful hardware accelerators that achieves the highest throughput, lowest latency and the greatest line-of-sight (LOS) and non-line-of-sight (NLOS) range in the industry even in the most challenging urban and industrial environments.

Available in the 3.5 GHz WiMAX band, the licensed 4.9 GHz public safety band or the 5.4 GHz - 5.8 GHz license exempt band, the AN-80i is configured via firmware options and throughput keys so you can purchase the features and throughput performance you need today between and upgrade later without having to replace any hardware. This common radio hardware approach reduces your spares requirement while providing a high level of future proofing via new firmware loads for updates and new features.

In the PTP configuration the AN-80i delivers over 100 Mbps Ethernet data rate— more than double the nearest competitor making it the ideal choice for high capacity backhaul applications. It has excellent range and is deployed in hundreds of links over 50 kms. In the PMP configuration, the AN-80i delivers over 50 Mbps Ethernet data rate, the highest in its class and it supports a full range of Quality of Service (QoS) controls to enable premium access services for voice, data and video services. Its industry leading capacity also supports the maximum number of video cameras with the highest video quality. With either configuration, you're assured of the ultra low latency - as low as 1 msec - up to 40 times lower versus the competition.

It provides AES-128 and AES-256 encryption, and X.509 certificate based authentication, and as the only broadband wireless solution to achieve FIPS 140-2 certification, the AN-80i delivers unparalleled security.

Designed to meet stringent carrier-class requirements, HALT accelerated life tested and with an IP67 (submersible) rated outdoor enclosure the AN-80i delivers industry-leading 29-year Mean Time Between Failures (MTBF) and the industry's lowest documented field failure rate , makes the AN-80i the perfect choice for mission critical deployments.

Available with a wide variety of antennas, the AN-80i includes an audible antenna alignment indicator, alignment mode GUI display and a built-in spectrum analyzer function for quick and simple installation. The product is manageable Over the Air (OTA) via a standard Web browser or through the Redline Management System (RMS), Redline's powerful, SNMP based element management system.

The unmatched capabilities of the AN-80i make it the ideal solution for broadband wireless backhaul and access applications where performance, security and reliability are paramount.

#### **Features:**

- Operates in 3.5 GHz WiMAX band,
  4.9 GHz public safety band and
  license-exempt 5.4 and 5.8 GHz bands
- Industry leading throughput –
  90 Mbps Ethernet PTO, 48 Mbps
  Ethernet PMP
- Exceptional long-range capabilities
- Highest capacity point-to-multipoint system in the industry
- Lowest end-to-end latency in its class
- Flexible channel size and speed selections
- QoS controls to segment and prioritize traffic groups
- Common hardware platform reduces spares
- Dynamic time division duplex TDD) transmission
- Easy install with IEEE 802.3af PoE

### **Industry-Leading Broadband Wireless Solutions**

Redline solutions deliver an unmatched combination of range, capacity, security, and reliability, even under the most challenging environmental conditions. Redline's best-in-class data rates and spectral efficiencies conserve valuable spectrum and reduce the cost of providing high-performance access. Redline solutions combine built-in security encryption with robust, extreme distance / high-bandwidth performance to deliver products that provide the reliability network operators and carriers need to grow their systems into the future.



# **AN-80i System Specifications**

System Capability:	LOS, optical-LOS, and non-LOS (OFDM)	Dynamic Channel Control: PTP - DFS, ATPC	
RF Band:	3.300 – 3.800 GHz <sup>1</sup> , TDD WiMAX licensed band		PMP - DFS
	4.940 – 4.990 GHz <sup>1</sup> , TDD licensed	Max Tx Power:	+25 dBm (region specific)
	Public Safety band	Rx Sensitivity:	-85 dBm @ 3 Mbps max.
	5.470-5.725 GHz <sup>1</sup> , TDD unlicensed band	PoE Cable:	Up to 91m (300 ft)
	5.725-5.850 GHz <sup>1</sup> , TDD unlicensed band	Network Connection:	10/100 Ethernet (RJ-45)
Channel Size:	5, 10, 20, 40 MHz <sup>1</sup> (software selectable)	System Configuration:	HTTP (Web) interface, SNMPv2, Telnet
Data Rate:	PTP - Up to 108 Mbps (uncoded burst rate),	Element Management:	RMS platform support
	PMP - Up to 54 Mbps (uncoded burst rate)	Operating Temp:	-40 to 60 degrees celcius
Network Attributes:	s: PTP - Transparent bridge, automatic link distance	Power Consumption:	Standard IEEE 802.3af (15.4 W Max.)
	ranging, 802.3x, 802.1p, DHCP pass-through	Power Supply:	110/220/240 VAC 50/60 Hz 18-60 VDC
	PMP - Transparent bridge, automatic link distance	Compliance:	IEC, EN, and UL/CSA 60950
	ranging, DHCP pass-through, 802.1Q VLAN, CIR,		EN 301 489-1, EN 301 489-17
	PIR support		5.8 GHz Industry Canada RSS 210,
	PTP -BPSK to 64 QAM bidirectional dynamic adaptive		FCC part 15, ETSI EN 302 502;
	PMP - BPSK to 64 QAM		5.4 GHz Industry Canada RSS 210,
	PTP - concatenation, ARQ		RSS 111, FCC part 15, ETSI EN 301 893
	PMP - concatenation, TDMA fragmentation, ARQ		FCC part 90 Industry Canada RSS 192,
Over the			FCC part 90, ETSI EN 302 326-2
	PTP - Proprietary private key	Dimensions:	11.38" L X 7.50" W X 2.03" H,
	encryption AES-128 and AES-256 options		28.9cm L X 19.0cm W X 5.15cm H
		Weight:	4.5 lbs, 2.0 kg

1. Availability restricted by regional regulations

# **About Redline Communications**

Redline Communications is the leading provider of advanced broadband wireless solutions. Redline's award-winning broadband wireless products enable network operators to cost-effectively support high bandwidth communications, including voice, video, and data communications. Redline is committed to maintaining its wireless industry leadership with the continued development of advanced wireless broadband products. Redline's experience and expertise helps service providers, utilities, oil and gas, government, military organizations and more roll out wireless broadband networks to support their specific communications requirements.